

## **SOFT CLEAN**

## **DESCRIPTION**

Soft Clean cleans all and degreases all materials quickly and effectively. Mixture of propellant and aliphatic hydrocarbon solvents. NSF-registration for use as a cleaner and degreaser for use in non food processing areas (K1).

#### **PROPERTIES**

- May be used on lacquered surfaces.
- Perfect body finish degreasing agent.
- Does not leave a thin layer of fat.
- Leaves no residue.
- Slow evaporation enables long action time.
- Safe on most surfaces.
- Penetrates into the dirt.
- Does not affect skin or rubber if it comes in brief contact with this product.
- Absolutely non-residual, almost instant evaporating and non corrosive.
- Green certified propellant with CO2 reduction up to 90%, naturally produced via organic waste = Green Propellant.

#### **FIELD OF APPLICATION**

- Cleaning and degreasing metals, glass and ceramics in workshops, industry and household.
- Removes moisture stains on metals.
- Cleaning prior to painting.
- · Cleaning prior to gluing.
- Removes sticker glue residues from cars, panels, etc.
- Removes silicone stains on metals.
- Suited for fast cleaning of disc and drum brakes, clutch components, bonding and sealing surfaces of lining dust, grease, oil, brake fluid, dirt, etc.
- As a cleaner and degreaser for use in non food processing areas. Which are
  used to remove oil, wax, resinous materials, or other substances not
  removable by using acidic or alkaline cleaning agents.

### **USER INSTRUCTIONS**

Spray on surface. Let it work and remove the dirt from the surface with a dry and clean cloth.



SOFT CLEAN – SOC – 86	Art.no. 25250-25256

Signature: JH Date: 2021-12-27





# **SOFT CLEAN**

## **TECHNICAL DETAILS**

PROFESSIONAL CLEANING SYSTEM

Color:	Clear.
Packaging:	500 ml tin plate aerosol: Art.no. 25250 5 liter Eco Box: Art.no. 25252 20 liter plastic bucket: Art.no. 25256 200 liter metal drum: Art.no. 25254
Accessories:	Tap 5I/15I Eco Box: Art.no. 35204 Tap 20I: Art.no. 35224 Air Mix Soft Clean: Art.no. 15215-6
Odor:	Solvent.
PH value:	n.a. (aliphatic hydrocarbons)
VOC (directive 2010/75/EU):	100 %
Density (20°C):	0,75 g/ml
Electrical resistance:	>15 x 10 <sup>12</sup> OHM (Omega)
Electric conductivity:	0,065 x 10 <sup>-12</sup> [S/m]
Shelf life (temp.) months (+5°C to +25°C):	24 months.
Application & Surface temperature:	-10°C to +50°C
Certificates & Registrations:	NSF K1, GREEN PROPELLANT.
Others:	In compliance with the legal regulations, please see current Material Safety Data Sheet. https://veidec.com/en/msds
User Instruction:	Scan the QR-code for MSDS, video and other information.





Reaction with: Resistant/ Resistant to a limited extent/ Not tested / Not resistant ACM - Acrylat rubber: resistant **CR - Chloroprene rubber:** resistant **CSM – Chlorosulfonated rubber:** resistant EPDM - Ethylene propylene diene rubber: resistant FKM - Fluorocaoutchoc resistant NBR - Nitrile butadiene rubber: resistant not tested NR - Natural rubber: resistant SBR - Styrene butadiene rubber:

SQM/MVQ - Silicone rubber:

resistant

SOFT CLEAN – SOC – 86	Art.no. 25250-25256
Signature: JH	Date: 2021-12-27

This product information is property of VEIDEC AB and is not to be forwarded to third persons without our agreement. The product information has been made out according to our experiences; the corresponding distributing company has to point out probable characteristics as to the use of the product as the application fields are often very different. The recommendations as to technical use are not binding and do not justify any contractual relationship and subsidiary obligations under the contract of purchase. They especially do not relieve the buyer from testing our product on his own as to the suitability for the designated field of application.